



CE



NEOELEC™ BPP130U

DEEP INDENTING HYDRAULIC TOOL
OPERATED ON BATTERY

18V
4Ah

DEEP INDENTING
16 > 240 mm²

HEXAGONAL CRIMPING
6 > 400 mm²

> Identical force, stroke and capacities as the H130 & XH130.

- ✓ **HEAD ACCORDING TO HN 68-S-90** (> EDF specifications)
For underground lines (bimetallic lugs and sleeves).
- ↔ **MAX. PASSAGE OF 34 mm**
In the head for large sections.
- ⚙ **MECHANICAL STOP (NEW FEATURE)**
The piston stops at stroke end.
- 🔄 **ROTATIVE HEAD**
270°

STROKE	26 mm
MAX. PASSAGE	34 mm
FORCE	130 kN
DIMENSIONS (L x l x h in mm)	415 x 75 x 310
WEIGHT (with battery)	6.300 kg



ASSEMBLY № 1
FOR INDENTING APPLICATION


 Refer to **PAGES 96**



ASSEMBLY № 2
FOR CRIMPING APPLICATION

130 kN crimping die sets can be used in this tool thanks to the adapter A12D2.

 Refer to **PAGES 89 – 95**



Opening dies



Indenter



Indenter holder PP130



Adapter A12D2



Die sets
6 > 400 mm²

> Common interchangeable indenter and opening dies for H130, XH130 & BPP130U.



> Case and charger delivered with the tool.
> **NEOELEC™** accessories
Refer to **PAGE 56 – 57.**